

SLOAN AG
 Birnmannsgasse 8
 CH-4009 Basel
 Switzerland
 Tel.: +41 (0) 61 264 10 60
 Fax: +41 (0) 61 264 10 75
 E-Mail: sloan@sloan-basel.com
 www.sloan-basel.com

T1^{3/4} LED's
 unbased

T1^{3/4} Leuchtdioden
 ungesockelt

T1^{3/4} Diodes lumineuses
 sans socle

All specifications according to information from our manufacturers, without additional guarantee on our part. Further types on request.

Alle Spezifikationen basieren auf Angaben unserer Lieferanten, ohne zusätzliche Garantie unsererseits. Weitere Typen auf Anfrage.

Toutes les spécifications selon indications de nos fabricants, sans garantie supplémentaire de notre part. Autres types sur demande.

L5
 No. 70



Actual size
 Grösse 1:1
 Echelle 1:1

The brightest

Package dimensions All dimensions are in millimeters	No.	Emitted colour	Epoxy of LED	Electro-optical characteristics Ta = 25°C										Price-code Preis-Code Code de prix	Type Typ Type	Resistor Widerstand Résistance		
				Peak Wave-length λ _p nm	Operat. Temp. °C	Stor. Temp. °C	Luminous intensity I _v			Forward voltage V _F			Code			V	mA	
							Viewing Angle	Typ. mcd	I _F mA	Typ. V	Max. V	I _F mA						
	70	Red Rot Rouge	CP	660	- 40 + 85	- 40 + 85	30°	500	20	1.85	2.5	20		R61F	O	without ohne sans		
		30°					1000	R71F										
		30°					2000	R91F										
		30°					3500	R91W										
		Yellow				595		+ 100	8°	2200		2.1	2.6		Y911	A	5	20
		Green Grün Vert	CP	565	- 40 + 85	- 40 + 85	30°	300	20	2.2	2.5	20		G51W	B	12	20	
		Green Grün Vert	CP	565	- 25 + 75	- 30 + 100	22°	1000	20	2.2	2.5	20		G71Q	C	18	20	
		Red Rot Rouge	CP	623	- 40 + 100	- 40 + 120	15°	3500	20	2.0	2.4	20		R812	D	24	20	
						6°	12 000- 16 000	R91H					E	28	20			
		Yellow Gelb Jaune	CP	594	- 40 + 100	- 40 + 120	6°	9300	20	2.0	2.4	20		Y91H	F	32	18	
		Red Rot Rouge	CP	660	- 25 + 85	- 30 + 100	15°	4000	20	2.0	2.5	20		R919	G	36	15	
		Yellow Gelb Jaune	CP	592	- 40 + 100	- 40 + 120	7°	3500	20	1.9	2.4	20		Y912	H	42	12	
Yellow Gelb Jaune	CP	592	- 40 + 100	- 40 + 120	24°	800	20	1.9	2.4	20		Y712						

Réserve de modifications de toutes les données techniques
 Änderungen die dem technischen Fortschritt dienen, sind vorbehalten
 Specifications subject to change without notice

① CP clear transparent / water clear
 TP transparent / colour clear
 WL white translucent / white diffused
 TL translucent / colour diffused

CP transparent klar
 TP farbig transparent
 WL weiss durchscheinend
 TL farbig durchscheinend

CP transparent clair
 TP transparent coloré
 WL transparent blanc
 TL transparent coloré

X separates Blatt

Order-code
 Bestell-code
 Code de commande

L5-